

THE ALL NEW KINTA 90 | 100



KINTA
THE ULTIMATE TRACTOR



Extended Warranty
Option Available:



A true partner in your tractor ownership and maintenance solution.

www.allplanters.com.my

Why choose Kinta 90 | 100 series?



About us

All-Planters Sdn. Bhd. is the sole distributor of KINTA Tractor in Southeast Asia and one of the leading tractor companies in Malaysia. We take pride in our high standards of after-sales services, boasting one of the largest service centres and highest professional standards in East and West Malaysia, as well as Indonesia.

Kinta 90 | 100

We offer various models under the Kinta 90 | 100 series ranging from models like Kinta 904, SB90, SB90 MK III, SB100 and SB 100 MK III to suit various user needs. Kinta Tractor Series also exceeds industry expectations in terms of safety, performance, reliability and will not only make the user's job more efficient but also provide additional working flexibility.



FAMOUS BRITISH DESIGN ENGINE



POWER DISC BRAKE SYSTEM*



8F/8R TRANSMISSION



CUSTOMISED JpV CLUTCH

All-Planters Implements Solution

With our Implements, each component and assembly is designed to ensure reliability and dependability in operations. Built from ground up specifically for the tough conditions in the region.

Benefits of our Implements

- Implements are built with quality assurance
- Availability of spare parts stocks
- Lower and manage user's cost
- Specifically designed for your needs

Kinta Hooklift Trailer

- Available in 10 - 12 tons
- Greater transport productivity, reliability and performance



General work

- Kinta tractor series are also multifunctional.
- A wide variety of implements choice from haulage, transportation, rotovation, mulching, plowing and many more



Jpv Agri-Grabber

- A highly durable 4 claw grabber which are available at 3 or 5 meters.
- Save cost and improve efficiency.
- Heavy duty design
- Reduce double handling, number of workers required and improve productivity of FFB evacuation



Bucket (Back Pusher)

- Length - 2800mm (8 feet)
- Depth - 610mm (2 feet)
- Height - 610mm (2 feet)

Specifications

		904	SB 90	SB 100
	Drive type	4WD	4WD	4WD
Engine	Engine model	YTO 4M5-T65Y-U2	YTO 4M5-T65Y-U2	YTO LR 4V5P-T65X-U2
	Number cylinders/cc	4 / 5130	4 / 5130	4 / 5610
	Engine power kW (hp)	66.00 (90)	66.00 (90)	73.50 (100)
	@ rated speed (rpm)	2300	2300	2300
	Max torque @ 1800 rpm	300Nm	300Nm	370-390Nm
	Compression ratio	19:01	19:01	18:01
PTO	PTO kW (hp)	30.62 (41.5)	30.62 (41.5)	30.62 (41.5)
	Type	Two Speed live PTO	Two Speed live PTO	Two Speed live PTO
	Shaft speeds	540/ 1000 rev/min 1000/ 2000 rev/min	540/ 1000 rev/min 1000/ 2000 rev/min	540/ 1000 rev/min 1000/ 2000 rev/min
	Shaft diameter	35 mm	35 mm	35 mm
	Configuration	6 spline	6 spline	6 spline
Clutch	Type	Single plate, dry, disc spring compress, Dual stage (Customised JPV Clutch)	Single plate, dry, disc spring compress, Dual stage (Customised JPV Clutch)	Single plate, dry, disc spring compress, Dual stage (Customised JPV Clutch)
Transmission	Type	Shuttle mesh with creeper gear	Shuttle mesh with creeper gear	Shuttle mesh with creeper gear
	Speeds	8 F x 8 R	8 F x 8 R	8 F x 8 R
	Normal speed range	10.04 -- 34.85 km/h	10.04 -- 34.85 km/h	10.04 -- 34.85 km/h
	Creeper speed range	2.33 -- 8.13 km/h	2.33 -- 8.13 km/h	2.33 -- 8.13 km/h
Hydraulic System	Functions	Draft position & Floating control	Draft position & Floating control	Draft position & Floating control
	Standard oil flow	36.8 lit / min	36.8 lit / min	36.8 lit / min
	Nominal pressure	16MPA ± 0.5	16MPA ± 0.5	16MPA ± 0.5
Three Point Linkage	Type	2 cat. ISO	2 cat. ISO	2 cat. ISO
	Max. Lift capacity	2600kg	2600kg	2600kg
Brakes and Steering	Brake type	Oil Immersed	Air over hydraulic power disc brake system	Air over hydraulic power disc brake system
	Options	-	Available in SB 90 MK III with Double Braking System of oil Immersed and power disc brake	Available in SB 100 MK III with Double Braking System of oil Immersed and power disc brake
	Steering type	Hydrostatic	Hydrostatic	Hydrostatic
Tyre Matrix	Rear tyres	18.4 X 30 or 16.9 X 34	18.4 X 30 or 16.9 X 34	18.4 X 30 or 16.9 X 34
	Front tyres	11.2 X 24	11.2 X 24	11.2 X 24
Dimensions/ Weight	Width (mm)	2810	2810	2810
	Height (mm)	2008	2008	2008
	Length (mm)	4296	4296	4296
	Wheel base (mm)	2200	2200	2200
	Weight with ballast (kg)	3750	3750	3750
Capacities	Fuel (litres)	100	100	100

Sole distributor:

All-Planters Sdn. Bhd.
no.17, Jalan Desa 2, Taman Desa,
86000, Kluang, Johor.
Malaysia.
Tel : + 607 777 1017
Fax : + 607 773 8778

Email : enquiry@allplanters.com.my

Every effort has been made to ensure that the information contained is accurate and current as possible.

