Precision engineered for exceptional results.

KINTA SB55 AGRICULTURE 4WD TRACTOR

LGP Tyre Option Available

Engineered For Performance, Get The Job Done Right

We are committed to delivering the best possible machine for our customers. We prioritize customer feedback and actively seek out input to design this our newest Kinta SB55 resulting in an all improved model to deliver high-performance results, even in the most challenging agricultural conditions. Kinta SB55 is engineered to tackle any terrain, providing unbeatable performance that gets the job done right all at a cost-effective way for the users.

PLANTERS

A true partner in your tractor ownership and maintenance solution.



www.allplanters.com.my

Specifications

ENGINETypeA498BT-36Engine Power HP(kW)55HP/ 40.5kWMax Torque (Nm)193Nm (Manufacturer's Estimate)Rated Engine Speed2400 rev/minNo. of Cylinders4Capacity (cc)3168Compression Ratio18:1AspirationNatural aspiratedTRANSMISSION12 Forward/ 12 Reverse or 8 Forward/ 8 ReverseSpeed12 Forward/ 12 Reverse or 8 Forward/ 8 ReverseNormal speed range9.036 - 31.37 km/hrCreeper speed range2.10 - 7.32km/hrTypeDual Stage PTOSpeed540 or 760 rev/min / Ground Speed OptionalShaft Diameter35mm
ArrS5HP/ 40.5kWEngine Power HP(kW)55HP/ 40.5kWMax Torque (Nm)193Nm (Manufacturer's Estimate)Rated Engine Speed2400 rev/minNo. of Cylinders4Capacity (cc)3168Compression Ratio18:1AspirationNatural aspiratedTRANSMISSION5TypeShuttle shift with creeper gearSpeed12 Forward/ 12 Reverse or 8 Forward/ 8 ReverseNormal speed range2.10 - 7.32km/hrTypeDual Stage PTOSpeed540 or 760 rev/min / Ground Speed OptionalShaft Diameter35mm
Max Torque (Nm)193Nm (Manufacturer's Estimate)Rated Engine Speed2400 rev/minNo. of Cylinders4Capacity (cc)3168Compression Ratio18:1AspirationNatural aspiratedTRANSMISSION12Speed12 Forward/ 12 Reverse or 8 Forward/ 8 ReverseNormal speed range9.036 - 31.37 km/hrCreeper speed range2.10 - 7.32km/hrTypeDual Stage PTOSpeed540 or 760 rev/min / Ground Speed OptionalShaft Diameter35mm
Rated Engine Speed2400 rev/minNo. of Cylinders4Capacity (cc)3168Compression Ratio18:1AspirationNatural aspiratedTRANSMISSIONTypeShuttle shift with creeper gearSpeed12 Forward/ 12 Reverse or 8 Forward/ 8 ReverseNormal speed range9.036 - 31.37 km/hrCreeper speed range2.10 - 7.32km/hrTypeDual Stage PTOSpeed540 or 760 rev/min / Ground Speed OptionalSpeed540 or 760 rev/min / Ground Speed Optional
No. of Cylinders4Capacity (cc)3168Compression Ratio18:1AspirationNatural aspiratedTRANSMISSIONTypeShuttle shift with creeper gearSpeed12 Forward/ 12 Reverse or 8 Forward/ 8 ReverseNormal speed range9.036 - 31.37 km/hrCreeper speed range2.10 - 7.32km/hrTypeDual Stage PTOSpeed540 or 760 rev/min / Ground Speed OptionalSpeed540 or 760 rev/min / Ground Speed Optional
Capacity (cc)3168Compression Ratio18:1AspirationNatural aspiratedTRANSMISSIONTransmitterTypeShuttle shift with creeper gearSpeed12 Forward/ 12 Reverse or 8 Forward/ 8 ReverseNormal speed range9.036 - 31.37 km/hrCreeper speed range2.10 - 7.32km/hrPTO1000000000000000000000000000000000000
Compression Ratio18:1AspirationNatural aspiratedTRANSMISSIONTypeTypeShuttle shift with creeper gearSpeed12 Forward/ 12 Reverse or 8 Forward/ 8 ReverseNormal speed range9.036 - 31.37 km/hrCreeper speed range2.10 - 7.32km/hrPTOTypeTypeDual Stage PTOSpeed540 or 760 rev/min / Ground Speed OptionalShaft Diameter35mm
AspirationNatural aspiratedTRANSMISSIONNatural aspiratedTypeShuttle shift with creeper gearSpeed12 Forward/ 12 Reverse or 8 Forward/ 8 ReverseNormal speed range9.036 - 31.37 km/hrCreeper speed range2.10 - 7.32km/hrPTODual Stage PTOSpeed540 or 760 rev/min / Ground Speed OptionalShaft Diameter35mm
TRANSMISSIONTypeShuttle shift with creeper gearSpeed12 Forward/ 12 Reverse or 8 Forward/ 8 ReverseNormal speed range9.036 - 31.37 km/hrCreeper speed range2.10 - 7.32km/hrPTOTypeSpeed540 or 760 rev/min / Ground Speed OptionalShaft Diameter35mm
TypeShuttle shift with creeper gearSpeed12 Forward/ 12 Reverse or 8 Forward/ 8 ReverseNormal speed range9.036 - 31.37 km/hrCreeper speed range2.10 - 7.32km/hrPTODual Stage PTOSpeed540 or 760 rev/min / Ground Speed OptionalShaft Diameter35mm
Speed12 Forward/ 12 Reverse or 8 Forward/ 8 ReverseNormal speed range9.036 - 31.37 km/hrCreeper speed range2.10 - 7.32km/hrPTODual Stage PTOTypeDual Stage PTOSpeed540 or 760 rev/min / Ground Speed OptionalShaft Diameter35mm
Normal speed range9.036 – 31.37 km/hrCreeper speed range2.10 – 7.32km/hrPTODual Stage PTOTypeDual Stage PTOSpeed540 or 760 rev/min / Ground Speed OptionalShaft Diameter35mm
Creeper speed range2.10 - 7.32km/hrPTODual Stage PTOTypeDual Stage PTOSpeed540 or 760 rev/min / Ground Speed OptionalShaft Diameter35mm
PTOTypeDual Stage PTOSpeed540 or 760 rev/min / Ground Speed OptionalShaft Diameter35mm
Type Dual Stage PTO Speed 540 or 760 rev/min / Ground Speed Optional Shaft Diameter 35mm
Speed 540 or 760 rev/min / Ground Speed Optional Shaft Diameter 35mm
Shaft Diameter 35mm
Configuration 6 Splines
CLUTCH
Type Single dry plate dual stage heavy duty customised JPV Clutch
HYDRAULICS
3-Point Linkage Control 2 Cat. ISO
Lift Capacity (max) 1030kg
Auxiliary (litres/min) 22
BRAKES AND STEERING
Brake Type Oil immersed mechanically operated together or independently
Steering Type Hydrostatic
SPOOL VALVES
Auxiliary 2
TYRE SIZE
Rear Tyres 12.4 x 28 / 14.9 x 24
Front Tyres 8.3 x 20
DIMENSION/ WEIGHTS
Width (mm) 1620
Length (mm) 3835
Wheelbase (mm) 2030
Weight with ballast (kg) 2126
Weight with ballast (kg) 2126

Sole distributor:

All-Planters Sdn.Bhd. No.18 Jalan Desa 2 , Taman Desa, 86000, Kluang, Johor. Malaysia. Tel : +607 777 1017 Fax : +607 773 8778

Email : enquiry@allplanters.com.my

Every effort has been made to ensure that the information contained is accurate and current as possible.





